

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-015-26226

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line

Section 35 Township 19S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3631' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8032'. Reached TD 4-5-90. Ran 193 joints 7" casing as follows: 13 jts 26# N-80, 21 jts 26# J-55, 23 jts 23# N-80, 121 jts 23# J-55, 12 jts 23# N-80 and 3 jts 26# J-55, casing set 8032'. Float shoe set 8032'. float collar set 7992'. DV tool set 5408'. Cemented Stage I - 500 gals Surebond, 700 sx Class H w/.8% CF-14 + 10% Salt + 5#/sx Hiseal (yield 1.19, wt 15.7). PD 12:15 PM 4-7-90. Circulated 100 sacks. Opened DV tool with 700 psi and circulated 2 hrs. Stage II - 825 sx Pacesetter Lite C w/5#/sx Salt + .4% CF-14 + 1/2#/sx Celloseal + 5#/sx Hiseal (yield 1.98, wt. 12.4). Tailed in w/100 sx Class H + .4% CF-14 + 5#/sx Salt (yield 1.19, wt 15.7). PD 3:45 PM 4-7-90. Closed tool with 3250 psi, held okay. Circulated 100 sx. Bumped plug to 1750 psi for 5 minutes, held okay. WOC 24 hours. WOCU.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-12-90

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 17 1990

CONDITIONS OF APPROVAL, IF ANY: