

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUMERICAL
OF COPIES REQUIRED
(Other instructions on
reverse side)

BLM Roswell District
Modified Form No.
NM60-3160-4

CLSF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	3. AREA CODE & PHONE NO. 915-684-7441	5. LEASE DESIGNATION AND SERIAL NO. NM-62998
2. NAME OF OPERATOR Maralo, Inc.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 832, Midland, Texas 79702	8. FARM OR LEASE NAME FEDERAL 6	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL and 1980' FWL of Section 6	10. FIELD AND POOL, OR WILDCAT Undes. East Lake Morrow	11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 6, T-19-S, R-27-E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3273.6' GL	12. COUNTY OR PARISH Eddy
		13. STATE New Mex.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	FILL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANE
(Other)	Casing Test

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	Casing Test

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded @ 12:00 a.m. 1/30/90.

1-31-90 Ran 8 jts. 13 3/8" J-55, 54.4# ST&C casing. Set @ 350'. Cemented w/350 sx Class C cement w/2% CaCl2. Circ. 90 sx to surface. WOC 26 hrs. Hole size 17 1/2"

2-6-90 Ran 54 jts. 8 5/8" casing. Set @ 2400'. Circ. 8 5/8" casing and cement w/1,150 sx HL cement w/1/4# floccle, + 2% CaCl2 + 400 sx Class C w/2% CaCl2. Cement circulated to surface. Witnessed by BLM. WOC 16 hrs. Tested casing to 1500 psi, ok. Hole size 12 1/4"

ACCEPTED FOR RECORD

DATE 2-12-90

18. I hereby certify that the foregoing is true and correct

SIGNED Brenda Coffman

TITLE Agent

DATE 2-12-90

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side