

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
 T. Salt _____
 B. Salt _____
 T. Yates _____
 T. 7 Rivers _____
 T. Queen _____
 T. Grayburg _____
 T. San Andres 542
 T. Glorieta _____
 T. Paddock YESO 2182
 T. Blinbry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abo _____
 T. Wolfcamp Lime-5430
 T. Penn _____
 T. Cisco (Bough C) _____

T. Canyon Lime 7564
 T. Strawn _____
 T. Atoka _____
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Delaware Sand _____
 T. Bone Springs Lime 3334
 T. _____
 T. _____
 T. _____

Northwestern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn "A" _____

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____
 No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	250	250	Surface, Gravel				
250	1300	1050	Gravel, Red Rock, Anhy				
1300	1440	140	Dolo, Anhy, Cht				
1440	2060	620	Dolo, Anhy				
2060	2300	240	Dolo, Anhy, Sd				
2300	2500	200	Dolo, Sd. Tr. Cht				
2500	2600	100	Dolo				
2600	2800	200	Dolo, Anhy, Sd				
2800	3320	520	SS, Dolo				
3320	3500	180	LS, Dolo, Sh				
3500	3580	80	LS, Sh				
3580	3800	220	LS				
3800	4640	840	LS, Sh				
4640	5370	730	SS, Dolo, Sh				
5370	5640	270	LS, Dolo, Cht				
5640	6220	580	LS, Sh				
6220	6600	380	LS, SS, Sh				
6600	7540	940	Sh, LS, Dolo, Sd				
7540	7640	100	LS, Cht, Sh				
7640	7880	240	Dolo				
7880	8040	160	LS, Sh, Trace SS				