

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

WELL API NO. 30-015-26250
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Foster FF Com
8. Well No. 2
9. Pool name or Wildcat North Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3605' GR

SUNDRY NOTICES AND REPORTS ON WELLS 1 5 1991
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT C. D.
(FORM C-101) FOR SUCH PROPOSALS.) ARTESIA OFFICE

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER Workover ☐
2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471
3. Address of Operator
105 South 4th St., Artesia, New Mexico 88210

4. Well Location
Unit Letter L : 1855 Feet From The South Line and 660 Feet From The West Line
Section 1 Township 20S Range 24E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: Add perforations, treat <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to add perforations to existing Canyon as follows:
TOOH w/sub-pump.
Perforate Canyon Dolomite as follows: 7863-76' (total 16 holes)
TIH w/tbg and packer. Set packer @ \pm 7830'.
Treat w/4000 gals 20% HCL acid.
Swab well and evaluate.

Existing perforations are: 7708-7772'
7806-7816'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-14-91
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

MAR 18 1991

CONDITIONS OF APPROVAL, IF ANY: