

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR MUMI
OF COPIES ROUTED
(Other instructions on re-
verse side)

MM Roswell District
Modified Form No.
MM60-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	3a. Area Code & Phone No. 505/740-1471	5. LEASE DESIGNATION AND SERIAL NO. NM 51828
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION	8. FARM OR LEASE NAME Nopal AFP Federal Com	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210	9. WELL NO. 1	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 1980' FWL, Sec. 35-19S-24E	10. FIELD AND POOL, OR WILDCAT Undesignated Morrow	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit N, Sec. 35-T19S-R24E
14. PERMIT NO. 30-015-26259	15. ELEVATIONS (Show whether DT, RT, GR, etc.) 3687' GR	12. COUNTY OR PARISH Eddy
		13. STATE NM

RECEIVED
JUN 15 90
C. C. D.
ARTESIA, OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5-7-90. Ran 29 joints 9-5/8" 36# J-55 casing, set at 1300'. Guide shoe set 1300', insert float set 1255'. Cemented w/900 sx Halliburton Lite + 10#/sx Hiseal + 1/2#/sx Floseal + 3% CaCl2 + 500 gals Flocheck (yield 1.84, wt 12.7)* PD at 7:30 PM 5-6-90. Bumped plug to 800 psi, float held okay. Cement did not circulate. Ran wireline. TOC at 109'. Used 10 yds redi-mix to surface. Drilled out 1:30 PM 5-7-90. WOC 18 hrs. Cut off and welded on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

* FOLLOWED WITH 200 SACKS CLASS 'C' CEMENT CONTAINING 2% CaCl2.
[REF. TELCON. WITH JUANITA Goodlett w/YATES ON 6/13/90]

ACCEPTED FOR RECORD

h2

JUN 13 1990

CARISBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNATURE *Juanita Goodlett*

TITLE Production Supervisor

DATE 6-4-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side