## Submit 3 Copies to Appropriate

CONDITIONS OF APPROVAL, IF ANY:

## State of New Mexico Energy, winerals and Natural Resources Department

Form C	-103
Revised	1-1-89

DISTRICT! P.O. Box 1980, Hobbs, NM 88240  OIL CONSERVATION DINGSHOP  WELL API NO.	<b></b>
P(1 HOV JIXX	\range \ran
NSTRICT II Santa Fe New Mexico 87504-2088 30-015-26265	
P.O. Drawer DD, Artesia, NM 88210  STATE  STATE	FEE X
1000 Rio Brazos Rd., Aztec, NM 87410  6. State Oil & Gas Lease No.	,
O. C. D.	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL	
2. Name of Operator YATES PETROLEUM CORPORATION 2 8. Well No. 2	
3. Address of Operator 9. Pool name or Wildcat	
105 South 4th St., Artesia, NM 88210 North Dagger Draw Uppe	r Penn
4. Well Location	
Unit Letter I: 1980 Feet From The South Line and 660 Feet From The East	Line
Section 25 Township 19S Range 24E NMPM Eddy	County
Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
//////////////////////////////////////	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABAND	ONMENT [
PULL OR ALTER CASING CASING TEST AND CEMENT JOB	
OTHER: Perforate and treat	<u> </u>
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 4-13-90. Drilled out DV tool. Spot 500 g. 20% NEFE acid. Perforated 7804-7819' w/holes as follows: 7804, 05, 06, 07, 12, 13, 14, 16, 17, 18 and 7819'. Pumped 12 bbl reverse acid, did not load. Set packer and tested to 500#. Swabbed well. 4-18-90. Open by-pass on packer, set packer. TOH. TIH w/7" RBP Uni VI. Set RBP @ tested to 500#. Spot 500 gals 20% NEFE acid. 4-19-90. Perforated 7675-7779' w/35 .42" holes as follows: 7675, 76, 77, 79, 81, 8 92, 93, 94, 95, 96 and 97 (14 holes); 7723, 25, 31, 32, 33, 37, 39, 40 and 41 (9 hol. 61, 62, 63, 64, 65, 71, 72,73, 77, 78 and 79' (12 holes). Acidized perforations in 3 2000 gals 20% NEFE acid. Move tools and straddle perfs 7804-19' and pump 200 gals acid. Unset packer and RBP. TOH. RU and perforated 7675-7779' w/124 .50" holes as 7675-97' (46 holes-2 SPF), 7723-41'(38 holes-2 SPF), 7760-79' (40 holes-2 SPF). Treatubing and casing w/20000 gals 20% NEFE and 1000# rock salt and Benzoic flakes (perf. 7819').	11 .41"  5 KCL to  7786' and  6, 87, 91,  es); 7760,  stages w/ 20% NEFE  follows: t down
I hereby certify that the information above in true and complete to the best of my knowledge and belief.	3 00
	0-90
SIGNATURE Production Supervisor DATE 4-30	0-90 05/748-147
SIGNATURE JUANITA GOODLETT Production Supervisor DATE 4-30  TYPE OR PRINT NAME JUANITA GOODLETT TELEPHONE NO. 5	
SIGNATURE Production Supervisor DATE 4-31	