

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

APR 2 '90

WELL API NO.

30-015-26290

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☒

GAS WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line

Section 14 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3617' GR

7. Lease Name or Unit Agreement Name

John AGU

8. Well No.

1

9. Pool name or Wildcat

Und. Morrow

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 3:00 PM 3-14-90 with rathole. Set 40' of 20" conductor. Notified Johnny Robinson, NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 3:00 PM 3-17-90. Notified Mike Stubblefield, NMOCD, Artesia, NM. Lost circulation at 234'. Mix and pump LCM pill. Ran 29 joints 9-5/8" 36# J-55 casing, set 1210'. Guide shoe set 1210', insert float 1170'. Cemented w/900 sx Halliburton Lite + 10#/sx Gilsonite + 1/2#/sx Flocele + 3% CaCl (yield 1.9, wt, 12.6). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 1:30 AM 3-20-90. Bumped plug to 800 psi, released pressure and float held okay. Cement did not circulate. WOC 5 hrs. Ran Temperature Survey and found TOC 150'. Ran 1". Tag cement 180'. Spotted 350 sx Class C w/4% CaCl2. PD 7:45 AM 3-20-90. Circulated 5 sx to pit. WOC. Drilled out 7:30 PM 3-20-90. WOC 17 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: *Juanita Goodlett*

TITLE Production Supervisor

DATE 3-30-90

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APR 4 1990

APPROVED BY SUPERVISOR, DISTRICT II

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: