to Appropriate District Office

State of New Mexico

10/-	L
Form C-103 C S - P	İ

TELEPHONE NO. 505/748-1471

4 1991

JAN

Submit 3 Copies Energy, Minerals and Natural Resources Department OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-26297 Santa Fe, New Mexico 87504-2088 DISTRICT II 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 DEC 27 '90 FEE X STATE 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS:SIA, OFFICE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Roy AET WELL X 2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION (505) 748-1471 9. Pool name or Wildcat 3. Address of Operator North Dagger Draw Upper Penn 105 South 4th St., Artesia, New Mexico 88210 Well Location ____ Line and 710 M . 710 Feet From The South Feet From The West Line 8 19S Eddy Range **NMPM** Section Township County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3582' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER Production Casing OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed TD 8250'. Reached TD 12-16-90. Ran 199 joints 7" casing set 8250' as follows: 14 jts 7" 26# N-80, 65 jts 7" 26# J-55, 95 jts 23# J-55, 20 jts 7" 23# N-80 and 5 jts 7" 26# J-55, casing set 8250'. Float shoe set 8250', float collar set 8205'. DV tool set 5394'. Marker joint at 7498'. Cemented 1st stage w/1100 sx "H" w/.8% CF-14, 10% salt and 5# Hiseal (yield 1.25, wt 15.6). PD 11:03 PM 12-17-90. Bumped plug to 2850 psi. Circulated 143 sx cement. Circulate thru DV tool 2 hrs. Cemented 2nd stage w/950 sx "C" Lite w/.4% CF-14, 5# salt and 5# Hiseal (yield 1.98, wt 12.40. Tailed in w/200 sx Class "H" Neat (yield 1.18, wt 15.7). PD 3:10 AM 12-18-90. Bumped plug to 3100 psi. Circulated 190 sx cement. WOC. WOCU 24 hrs. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 12-24-90 Production Supervisor

(This space for State Use)

APPROVED BY-

TYPEORPRINTNAME Juanita Goodlett

ORIGINAL SIGNED BY

SUPERVISOR, DISTRICT IT

MIKE WILLIAMS