Submit 3 Copies	Stat	te of New Mexic	co	x	CIST Form C-103	1
o Appropriate District Office	Energy, humerals a	nd Natural Reso	urces Department	4	Wised 1-1-	D 7
DISTRICT 1 P.O. Box 1980, Hobbs, NM 88240		P.O. Box 2088		WELL API NO.)-015-26300	
<u>DISTRICT II</u> P.O. Drawer DD, Artesia, NM 88210	Santa Fe, N	lew Mexico 87	7504-2088	5. Indicate Type	of Lease	FEE
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 874	410		بر رون (۱۹۹۵)	6. State Oil & G	as Lease No. LG-1525	
(DO NOT USE THIS FORM FOR	NOTICES AND REPOR R PROPOSALS TO DRILL C RESERVOIR. USE "APPLIC/ RM C-101) FOR SUCH PRC	ATION FOR PERM	H PLUG BACK ICA	7. Lease Name of	or Unit Agreement Name	
1. Type of Well: OR OAS WELL WELL	L X on		2011년 1931년 1911년 - 1931년 1931년 1911년 - 1931년		State CO Com	
2. Name of Operator	DOD ATT ON		*	8. Well No.	4	
YATES PETROLEUM COR	RPORATION		- Chester -	9. Pool name or	Wildcat	
3. Address of Operator 105 South 4th St.,	Artesia, NM 882	10	C		gnated Morrow	
4. Well Location	1980 Feet From The	North	Line and198	30 Feet Fro	om The <u>West</u>	Line
	Townshin 19	C Dame	e 24E	NMPM	Eddy	County
Section 36	Township 19	S Ran on (Show whether D	F, RKB, RT, GR, etc.)			
			622' GR			
11. Ch	eck Appropriate Box	to Indicate N	lature of Notice,	Report, or Oth	PEROPT OF	
NOTICE OF	F INTENTION TO:		SU	BSEQUENT	REPORT OF:	 1
						1
	PLUG AND AB	IANDON LI	REMEDIAL WORK		ALTERING CASING	
			REMEDIAL WORK		ALTERING CASING	
TEMPORARILY ABANDON	PLUG AND AB CHANGE PLAI					
TEMPORARILY ABANDON			COMMENCE DRILLI		PLUG AND ABANDC	
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:	CHANGE PLAN	NS 🗌	COMMENCE DRILLI CASING TEST AND OTHER:Perfor	CEMENT JOB	PLUG AND ABANDO	X
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Complete work) SEE RULE 1103. 6-21-2000 - Moved and tested. Nippl 6105'. Shut well 6-22-2000 - Finish up power swivel. Displaced hole wir wireline. TIH wi rigged down wirel. 6-23-2000 - Shut 6-24-25-2000 - Ri	CHANGE PLAN CHANGE PLAN Change PLAN Compensions (Clearly state all) in and rigged up led up 5K hydraul in. hed TIH with bit, Drilled cement t th treated water. th logging tools ine. in. gged up wireline.	peninent details, and pulling un ic BOP. The drill colf co 9367'. The TOOH with and ran GR, TIH with	COMMENCE DRILLI CASING TEST AND OTHER: Perfor d give pertinent dates, int nit and revers IH with bit, d lars and tubin Tagged float of h bit, drill of /CBL/CCL log. 3-1/8" casing	CEMENT JOB ate, acidiz cluding estimated dat se unit equidrill collar and tagged collar. Cir collars and TOOH with g guns and H th Arrowset	PLUG AND ABANDO <u>e & frac</u> <u>re of starting any proposed</u> pment. Set one is and tubing to ed up at 9345'. culated hole c tubing. Rigge logging tools perforated 9302 II packer and	Rigged lean. d up and -9338' 2-3/8"
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Complete work) SEE RULE 1103. 6-21-2000 - Moved and tested. Nippl 6105'. Shut well 6-22-2000 - Finish up power swivel. Displaced hole wir wireline. TIH wir rigged down wirel. 6-23-2000 - Shut 6-23-2000 - Shut 6-24-25-2000 - Rit w/10.42" holes (seating nipple on Pumped 3-1/2 bbls tree. Packer sti	CHANGE PLAN CHANGE PLAN Change PLAN Compensions (Clearly state all in and rigged up led up 5K hydraul in. hed TIH with bit, Drilled cement t th treated water. th logging tools ine. in. gged up wireline. Chester). Rigged tubing to 9250'. and pressured up 11 set. Worked p	NS	COMMENCE DRILLI CASING TEST AND OTHER: Perfor d give periment dates, in hit and revers IH with bit, of lars and tubin Tagged float of h bit, drill of /CBL/CCL log. 3-1/8" casing line. TIH wi er. Nippled si. Circulat t 1800K. Nip	CEMENT JOB ate, acidiz cluding estimated dat se unit equidrill collar and tagged collar. Cirr collars and TOOH with g guns and p th Arrowset down BOP and e around bac pled up tree	PLUG AND ABANDO <u>e & frac</u> <u>e of starting any proposed</u> pment. Set one is and tubing to ed up at 9345'. culated hole c tubing. Rigge logging tools perforated 9302 II packer and d nippled up tr ckside. Nipple e. Pumped to 2	Rigged lean. d up and -9338' 2-3/8" ee. d down 500 ps1.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Complete work) SEE RULE 1103. 6-21-2000 - Moved and tested. Nippl 6105'. Shut well 6-22-2000 - Finish up power swivel. Displaced hole wir wireline. TIH wir rigged down wirel. 6-23-2000 - Shut 6-23-2000 - Shut 6-24-25-2000 - Rit w/10.42" holes (seating nipple on Pumped 3-1/2 bbls tree. Packer sti	CHANGE PLAN CHANGE PLAN Change PLAN Compensions (Clearly state all in and rigged up led up 5K hydraul in. hed TIH with bit, Drilled cement t th treated water. th logging tools ine. in. gged up wireline. Chester). Rigged tubing to 9250'. and pressured up 11 set. Worked p	NS	COMMENCE DRILLI CASING TEST AND OTHER: Perfor d give pertinent dates, ind nit and revers IH with bit, of lars and tubin Tagged float of h bit, drill of /CBL/CCL log. 3-1/8" casing line. TIH wi er. Nippled si. Circulat t 1800K. Nip	CEMENT JOB ate, acidiz cluding estimated dat se unit equidrill collar and tagged collar. Cir collars and TOOH with g guns and p th Arrowset down BOP and e around bac pled up tree CONTINUE	PLUG AND ABANDO e & frac e of starting any proposed pment. Set one cand tubing to ed up at 9345'. cculated hole c tubing. Rigge logging tools perforated 9302 II packer and d nippled up tr ckside. Nipple e. Pumped to 2 D ON NEXT PAGE:	Rigged lean. d up and -9338' 2-3/8" ee. d down 500 psi.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Complete work) SEE RULE 1103. 6-21-2000 - Moved and tested. Nippl 6105'. Shut well 6-22-2000 - Finish up power swivel. Displaced hole wir wireline. TIH wir rigged down wirel 6-23-2000 - Shut 6-24-25-2000 - Rit w/10.42" holes (seating nipple on	CHANGE PLAN CHANGE PLAN Change PLAN Compensions (Clearly state all in and rigged up led up 5K hydraul in. hed TIH with bit, Drilled cement t th treated water. th logging tools ine. in. gged up wireline. Chester). Rigged tubing to 9250'. and pressured up 11 set. Worked p	NS	COMMENCE DRILLI CASING TEST AND OTHER: Perfor d give pertinent dates, ind nit and revers IH with bit, of lars and tubin Tagged float of h bit, drill of /CBL/CCL log. 3-1/8" casing line. TIH wi er. Nippled si. Circulat t 1800K. Nip	CEMENT JOB ate, acidiz cluding estimated dat se unit equidrill collar and tagged collar. Cir collars and TOOH with g guns and p th Arrowset down BOP and e around bac pled up tree CONTINUE	PLUG AND ABANDO e & frac fe of starting any proposed pment. Set one and tubing to and tubing to and tubing to and tubing. Rigge logging tools perforated 9302 II packer and d nippled up tr ckside. Nipple e. Pumped to 2 D ON NEXT PAGE: DATE July 3	<pre>X e anchor o Rigged lean. d up and -9338' 2-3/8" ee. d down 500 ps1. 01, 2000</pre>
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Complete work) SEE RULE 1103. 6-21-2000 - Moved and tested. Nipp1 6105'. Shut well 6-22-2000 - Finish up power swivel. Displaced hole wit wireline. TIH wither rigged down wirel 6-23-2000 - Shut 6-24-25-2000 - Rither w/10.42" holes (seating nipple on Pumped 3-1/2 bbls tree. Pacter sti I hereby cartify the de information at SKINATURE	CHANGE PLAN CHANGE PLAN Change PLAN Compensions (Clearly state all in and rigged up led up 5K hydraul in. hed TIH with bit, Drilled cement t th treated water. th logging tools ine. in. gged up wireline. Chester). Rigged tubing to 9250'. and pressured up 11 set. Worked p	NS	COMMENCE DRILLI CASING TEST AND OTHER: Perfor d give pertinent dates, ind nit and revers IH with bit, of lars and tubin Tagged float of h bit, drill of /CBL/CCL log. 3-1/8" casing line. TIH wi er. Nippled si. Circulat t 1800K. Nip	CEMENT JOB ate, acidiz cluding estimated dat se unit equidrill collar and tagged collar. Cir collars and TOOH with g guns and p th Arrowset down BOP and e around bac pled up tree CONTINUE	PLUG AND ABANDO e & frac e of starting any proposed pment. Set one is and tubing to ed up at 9345'. culated hole c tubing. Rigge logging tools perforated 9302 II packer and d nippled up tr ckside. Nipple e. Pumped to 2 D ON NEXT PAGE:	<pre>X e anchor o Rigged lean. d up and -9338' 2-3/8" ee. d down 500 psi. 01, 2000</pre>
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Complete work) SEE RULE 1103. 6-21-2000 - Moved and tested. Nippl 6105'. Shut well 6-22-2000 - Finish up power swivel. Displaced hole wir wireline. TIH wir rigged down wirel. 6-23-2000 - Shut 6-24-25-2000 - Rit w/10.42" holes (seating nipple on Pumped 3-1/2 bbls tree. Packer sti I hereby cartify the dre information at skinnature Rusty TYPE OR FRINT NAME Rusty	CHANGE PLAN CHANGE PLAN Change PLAN Change of the state all in and rigged up led up 5K hydraul in. hed TIH with bit, Drilled cement the th treated water. th logging tools ine. in. gged up wireline. Chester). Rigged tubing to 9250'. and pressured up 11 set. Worked p	NS	COMMENCE DRILLI CASING TEST AND OTHER: Perfor d give pertinent dates, ind nit and revers IH with bit, of lars and tubin Tagged float of h bit, drill of /CBL/CCL log. 3-1/8" casing line. TIH wi er. Nippled si. Circulat t 1800K. Nip	CEMENT JOB ate, acidiz cluding estimated dat se unit equidrill collar and tagged collar. Cir collars and TOOH with g guns and p th Arrowset down BOP and e around bac pled up tree CONTINUE	PLUG AND ABANDO e & frac fe of starting any proposed pment. Set one and tubing to and tubing to and tubing to and tubing. Rigge logging tools perforated 9302 II packer and d nippled up tr ckside. Nipple e. Pumped to 2 D ON NEXT PAGE: DATE July 3	X e anchor o Rigged lean. d up and -9338' 2-3/8" ee. d down 500 psi. 500 psi. 01, 2000