

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUM
OF COPIES REQUIRED
(Other instructions on re-
verse side)

151
BIM Roswell District
Modified Form No.
NM60-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		3a. Area Code & Phone No. 505/748-1471		5. LEASE DESIGNATION AND SERIAL NO. NM 043625
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION		3b. <i>JUN 19 1990</i>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		8. FARM OR LEASE NAME Saguaro AGS Federal Com		7. UNIT AGREEMENT NAME N/A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL, 1980' FWL, Sec. 15-T20S-R24E		9. WELL NO. 2		10. FIELD AND POOL, OR WILDCAT South Dagger Draw Upper Penn
14. PERMIT NO. 30-015-26310		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3677' GR		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit F, Sec. 15-20S-24E
		12. COUNTY OR PARISH Eddy		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input checked="" type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <input type="checkbox"/> Production Casing, Perforate	<input checked="" type="checkbox"/>

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 9440'. Reached TD 5-12-90. Ran 228 joints 7" casing as follows: 48 jts 7" 26# N-80 LT&C, 21 jts 7" 26# J-55 LT&C, 23 jts 7" 23# N-80 LT&C, 78 jts 7" 23# J-55 LT&C, 55 jts 7" 23# N-80 LT&C and 3 jts 7" 26# N-80 LT&C, casing set 9440'. Float shoe set 9440', float collar set 9400' DV tool set 5368'. Cemented stage 1: 500 gals WMW 1 and 500 gals Surebond. Tailed in w/1475 sx Class H .8% CF-14, 5#/salt, 1/2# Celloseal and 5# Hyseal (yield 1.19, wt 15.7). PD 11:45 AM 5-14-90. Circulated thru DV tool for 2 hrs. Circulated 66 sx. Stage 2: 960 sx Pacesetter Lite C .4% CF-14, 5#/salt, 1/2# Celloseal and 5# Hyseal (yield 1.99, wt 12.4). Tailed in w/ 100 sx Class H Neat (yield 1.18, wt 15.6). PD 3:15 PM 5-14-90. Bumped plug to 3400 psi. Float held okay. Circulated 75 sacks to pit on 2nd stage. WOC. 5-23-90 - 5-25-90. Drilled out DV tool at 5368'. TIH with tubing to 7702'. Spot 500 g. 20% NEFE acid. Perforated 7551-7693' w/16 - .50" holes as follows: 7551, 53, 55, 7579, 80, 81, 7617, 18, 19, 7655, 57, 59, 61, 7689, 91, and 7693'. Acidized perforations 7551-7693' in 4 stages w/1200 gals 20% HCL.

ACCEPTED FOR RECORD

JUN 15 1990

CARLSBAD, NEW MEXICO

RECEIVED
JUN 7 10 50 AM '90
CARLSBAD DISTRICT
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE Production Supervisor

DATE 6-5-90

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side