YATES PETROLEUM CORPORATION

Hill View "AHE" Fed. Com. #1 660' FNL & 660' FWL Section 12-T20S-R24E Eddy County, New Mexico

In conjunction with Form 3160-3, Application for Permit to Drill subject well, Yates Petroleum Corporation submits the following ten items of pertinent information in accordance with USCS requirements.

- 1. The geological surface formation is alluvium.
- 2. The estimated tops of geologic markers are as follows:

San Andres	555'
Glorieta	2127'
Bone Spring	3473'
Wolfcamp Lime	5472'
Canyon	7607'
Canyon Dolomite	7690 '
Base Dolmite	795C'
TD Canyon	8150'

3. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Water: Approximately 275'

Oil or Gas: Wolfcamp, Canyon

- 4. Proposed Casing Program: See Form 3160-3.
- 5. Pressure Control Equipment: See Form 3160-3.
- 6. Mud Program: See Form 3160-3.
- 7. Auxiliary Equipment: Kelly Cock; pit level indicators and flow sensor equipment; sub with full-opening valve on floor, drill pipe connection.
- 8. Testing, Logging and Coring Program:

Samples: 10' samples out from under surface casing to TD.
DST's: As warranted
Coring: None
Logging: CNL-LDT from TD to casing with GR-CNL up to surface; DLL (with min RXO)
from TD to casing; possible long spaced sonic.

- 9. No abnormal pressures or temperatures are anticipated.
- 10. Anticipated starting date: As soon as possible after approval.