

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING  
OFFICE FOR NUMBER  
OF COPIES REQUIRED  
(Other instructions on re-  
verse side)

MM Roswell District  
Modified Form No.  
NM060-3160-4

c/sf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3a. AREA CODE Phone No. 505/748-1471		5. LEASE DESIGNATION AND SERIAL NO. NM 045274	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210				7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 660' FWL, Sec. 12-T20S-R24E		MAY - 3 '90		8. FARM OR LEASE NAME Hill View AHE Federal Com	
14. PERMIT NO. 30-015-26335		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3595' GR		9. WELL NO. 1	
				10. FIELD AND POOL, OR WILDCAT North Dagger Draw Upper Penn	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA Unit D, Sec. 12-20S-24E	
				12. COUNTY OR PARISH Eddy	
				13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole at 9:30 AM 4-19-90 w/Frank's Rathole. Set 40' of 20" conductor. Redi-mix w/4 yds. Notified BLM, Carlsbad, NM of spud. Moved in rotary tools and resumed drilling 14-3/4" hole 8:00 AM 4-22-90. Notified BLM Answering Service, Carlsbad, NM. Lost circulation at 135'. Drilling at 1170' dry. Received permission from Adam Salameh, BLM Carlsbad, NM, to TD 14-3/4" hole at 1177'.

4-24-90. Ran 28 joints 9-5/8" 36# J-55 casing set at 1183'. Guide shoe set 1183', insert float set 1140'. Cemented w/1000 gal Flocheck, 900 sx Halliburton Lite + 10#/sx Gilsonite, 1/2#/sx Floseal and 3% CaCl2, (yield 1.98, wt 12.4). Tailed in w/200 sx Class "C" w/2% CaCl2. (yield 1.32, wt 14.8). PD 2:45 PM 4-24-90. Bumped plug to 600 psi, held okay. Cement did not circulate. Top of cement at 80', ready-mix to surface. NOTE: Permission obtained from Jim Amos, BLM, Carlsbad, NM. Cement baskets set 218' and 481'. Fluid level at TD was 70'. Ready mix to surface.

WOC. Drilled out 8:45 AM 4-25-90. WOC 17 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Drilled plug and resumed drilling.

ACCEPTED FOR RECORD

AsE

MAY 1 1990

NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Yvonne D. Dodds

TITLE Production Supervisor

DATE 4-26-90

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side