

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions on re-
verse side)

BLM Roswell District
Modified Form No.
NMOG-3160-4

c/57

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input checked="" type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. UNIT ACREAGE NAME JUN 22 90	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION		8. FARM OR LEASE NAME Roden Federal	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		9. 6	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL & 660' FEL, Sec. 35-19S-24E		10. FIELD AND POOL, OR WILDCAT North Dagger Draw Upper Penn	
14. PERMIT NO. 30-015-26337		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3646' GR	
12. COUNTY OR PARISH Eddy		13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Reconpletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded with rathole 1:10 PM 6-4-90. Set 40' of 20" conductor. Notified Kathy, BLM, Carlsbad, NM of spud. Resumed drilling 14-3/4" hole 6:15 PM 6-6-90. Notified BLM, Carlsbad, NM answering service. Lost circulation 639'. Dry drilling 1145'.
6-9-90. Ran 29 joints 9-5/8" 36# J-55 casing set 1270'. Guide shoe set 1270', insert float set 1226'. Cemented w/900 sx Pacesetter Lite w/10#/sx Hiseal + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.98, wt. 12.6). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 5:15 PM 6-9-90. Bumped plug to 750 psi, float did not hold. Pressure to 500 psi. Shut valve on manifold for 4 hrs. Circulated 0 sacks cement. WOC. Drilled out 11:15 AM 6-10-90. WOC 18 hrs. NU and tested to 1000 psi for 20 minutes. Reduced hole to 8-3/4" and resumed drilling.
Note: Cement baskets at 656' and 346'.

* RAN 1" AND CEMENTED WITH 370 SACKS CLASS "C"
W/ 4% CaCl2. CIRC. 10 SX TO SURFACE.
(REF: TEL. CONN. BETWEEN JUANITA Goodlett AND ADAM
TAMM ON 6/19/90).

RECEIVED

JUN 13 10 33 AM '90

18. I hereby certify that the foregoing is true and correct

SIGNED Juanita Goodlett

TITLE Production Supvr.

DATE 6-12-90

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO