Submit 3 Copies

State of New Mexico

Form C-103

inerals and Natural Resources Department Revised 1-1-89 Energy to Appropriate District Office OIL CONSERVATION DIVISION DISTRICT I WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 RECEIVED 30-015-26342 Santa Fe. New Mexico 87504-2088 DISTRICT II 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE X STATE AUG 15 '90 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS 🔍 🛴 🖫 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUS PASKITO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Ceniza AGZ Com WELL X OTHER 8. Well No. 2. Name of Operator YATES PETROLEUM CORPORATION 9. Pool name or Wildcat 3. Address of Operator Und. North Dagger Draw Upper 105 South 4th St., Artesia, NM /Penn 4. Well Location Line and $_660$ Feet From The East 660 South Line _ Feet From The County 24E NMPM Eddy Range Township Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3608' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: **ALTERING CASING** REMEDIAL WORK PERFORM REMEDIAL WORK PLUG AND ABANDON PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. CHANGE PLANS TEMPORARILY ABANDON CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER:_ OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spud 26" hole 3:30 PM 8-2-90 with rathole. Set 40' of 20" conductor. Notified Betty Rollins, NMOCD, Artesia, NM of spud. Resumed drilling 14-3/4" hole 6:00 AM 8-3-90. Notified NMOCD, answering service. Ran 30 joints 9-5/8" 36# J-55 casing set 1305'. Guide shoe set 1305', insert float set 1262'. Cemented w/900 sx Pacesetter Lite w/10#/sx Hiseal, 1/2#/sx Celloseal and 3% CaCl2 (yield 1.98, 12.4). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 5:45 PM 8-6-90. Bumped plug to 900 psi, released pressure and float held okay. Circulated 100 sacks. WOC. Drilled out 5:00 PM 8-7-90. WOC 23 hrs and 15 mins. NU and tested to 3000 psi for 50 minutes, OK. Reduced hole to 8-3/4". Resumed drilling. I hereby certify that the information above is trite and complete to the best of my knowledge and belief. TIME Production Supervisor DATE 8-13-90 Dodlet

Juanita Goodlett TYPE OR PRINT NAME (This space for State Use) ORIGINAL SIGNED BY MIKE WILLIAMS

SUPERVISOR, DISTRICT IT

_ TITLE -

AUG 2 0 1990

TELEPHONE NO. 505/748-1471

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY --