

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO. *45F*

NM-61590

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Parkway 30 Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Und. Parkway Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, 19S, 30E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

MAY 17 '90

ARTESIA, OFFICE

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Santa Fe Energy Operating Partners, L.P.

3. ADDRESS OF OPERATOR

500 W. Illinois, Suite 500, Midland, TX 79701 C. C. D.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

660' FNL and 660' FWL, Sec. 30, T-19S, R-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

3354.8' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Spud and set casing ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-30-90: Spud well at 12:15 p.m. CST

5-2-90: Depth 370'. RU and ran 9 jts 18-5/8" 87.5# K-55 casing and set at 365'.

5-3-90: Cemented 18-5/8" casing w/ 100 sx "C" Thickset and tail w/ 650 sx Class "C" containing 2% CaCl₂. WOC 8 hours. Ran temp survey and found TOC at 50'. WOC 2½ hours. Cut off 18-5/8" and cement w/ 7-1/2 yds Redi-mix. Weld on flowline. WOC (Redi-mix) 4½ hours. Resume drilling operations.

ACCEPTED FOR RECORD

MAY 11 1990

CARLSBAD, NEW MEXICO

RECEIVED
MAY 7 8 05 AM '90
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Jerry McCullough

TITLE

Sr. Production Clerk

DATE

May 4, 1990

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side