

(November 1983)  
(Formerly 9-331)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-61590

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Parkway 30 Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Und. Parkway Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T-19S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Santa Fe Energy Operating Partners, L.P.

3. ADDRESS OF OPERATOR

500 W. Illinois, Suite 500, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FNL and 660' FWL, Sec. 30, T-19S, R-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3354.8' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Ran casing string

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

XX

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

5-12-90: (Depth 3200'). Ran 78 jts. 8-5/8" 24#, K-55 ST&C casing and set at 3200'.

5-13-90: Cemented w/ 900 sx Howco Lite and 350 sx Cl. C w/ 2% CaCl<sub>2</sub>. Ran temperature survey. Top of cement at 680'. Pick up 1" and cement w/ 300 sx Cl. C w/ 2% CaCl<sub>2</sub>. Circulated 10 sx to surface. WOC.

5-14-90: WOC total of 13 hours. Tested casing and Hydrill to 600# - okay. Resume drilling operations.

RECEIVED  
MAY 22 12 01 PM '90  
CATTLE AREA

ACCEPTED FOR RECORD

APR

MAY 21 1990

CARSBED, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*James McCullough*

TITLE Sr. Production Clerk

DATE May 21, 1990

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side