

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy		T. Canyon	7472
T. Salt		T. Strawn	8122
B. Salt		T. Atoka	8730
T. Yates		T. Miss	
T. 7 Rivers		T. Devonian	
T. Queen		T. Silurian	
T. Grayburg		T. Montoya	
T. San Andres	458	T. Simpson	
T. Glorieta	2006	T. McKee	
T. Paddock	YESO 2089	T. Ellenburger	
T. Blinbry		T. Gr. Wash	
T. Tubb		T. Delaware Sand	
T. Drinkard		T. Bone Springs	3304
T. Abo	4908	T. Morrow Clastic	9084
T. Wolfcamp	5502	T. Chester	9389
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo		T. Penn. "B"	
T. Kirtland-Fruitland		T. Penn. "C"	
T. Pictured Cliffs		T. Penn. "D"	
T. Cliff House		T. Leadville	
T. Menefee		T. Madison	
T. Point Lookout		T. Elbert	
T. Mancos		T. McCracken	
T. Gallup		T. Ignacio Otzte	
Base Greenhorn		T. Granite	
T. Dakota		T.	
T. Morrison		T.	
T. Todilto		T.	
T. Entrada		T.	
T. Wingate		T.	
T. Chinle		T.	
T. Permian		T.	
T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface - Rock	5600	5946	346	Lm, Sh
40	1205	1165	Dolo	5946	6600	654	Lm, Sh, Sd
1205	1490	285	Cht, Dolo, Sh	6600	7020	420	Sh, Sd
1490	1790	300	Dolo, Cht	7020	7182	162	Sh
1790	1990	200	Dolo	7182	7250	68	Sd, Sh
1990	2270	280	Dolo, Sd	7250	7460	210	Sh, Dolo
2270	2430	160	Dolo, Sh	7460	7920	460	Lm, Sh, Dolo, Sd
2430	2770	340	Dolo	7920	8080	160	Sh, Dolo, LS
2770	2870	100	Dolo, Sd	8080	9080	1000	LS, Sh
2870	3070	200	Cht, Dolo, Sh	9080	9340	260	Sd, Sh, LS
3070	3308	238	Dolo	9340	9487	147	Sh, LS
3308	3530	222	Lm, Sh, Dolo				
3530	4570	1040	Lm, Sh				
4570	4940	370	Dolo, Lm, Sd				
4940	5070	130	Dolo				
5070	5126	56	Sh				
5126	5600	474	Sh, Lm, Dolo				