

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-26401
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-9739-19
7. Lease Name or Unit Agreement Name	SAND DUNE STATE
8. Well No.	5
9. Pool name or Wildcat	TURKEY TRACK SR-Q-G-SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED JUL 24 '90 O. C. D. ARTESIA. OFFICE
2. Name of Operator MYCO INDUSTRIES, INC.	
3. Address of Operator 207 SCUTH 4th. ARTESIA, NM 88210	
4. Well Location Unit Letter N : 990' Feet From The SOUTH Line and 1980' Feet From The WEST Line Section 11 Township 19s Range 29e NM/PM EDDY County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3375' GR. 3383' KB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	

AFT RIG # 2 SPUD A 12 1/4" HOLE AT 4:00 PM 7/16/90 LC AT 45' DRILLED TO TD 350'.  
RAN 8 JTS. 337' NEW 8 5/8" 23 # J-55 CASING W/ TEXAS PATTERN GUIDE SHOE SET AT 350'  
AND INSERT FLOAT AT 306.46' & CEMENTED W/ 250 SXS HOWCO PREMIUM PLUS W/ 2 % CaCl  
PLUG DOWN 6:30 AM 7/17/90 DID NOT CIRCULATE, READY-MIX TO SURFACE W/ 15 YDS.  
WOC 18 HRS. PRESSURE TESTED TO 800 # HELD OK.  
DRILLED OUT W/ 7 7/8" BIT AND DRILLED TO TD 2460' KB, RAN OPEN HOLE LOGS, LDT/CNL,  
DLL/RXO TO 2460'. RAN 68 JTS. 2636.5' OF NEW 5 1/2" 15.5 # K-55 LT & C CASING W/  
GUIDE SHOE SET AT 2637.5' KB, FLOAT COLLAR SET AT 2595' KB, CEMENTED W/ 375 SXS HOWCO  
LITE W/ 12 # SALT & 1/4 # FLOCELE PER SK. + 300 SXS HOWCO PREMIUM PLUS W/ 5 # SALT &  
.3 % HALAD 4, + .2 % CFR 3 PER SK. PLUG DOWN AT 10:15 PM 7/22/90. CIRCULATED 75 SXS.

NOW WAITING ON COMPLETION UNIT

I hereby certify that the information above is true and complete to the best of my knowledge and belief

SIGNATURE W.A. Gressett TITLE CONSULTANT DATE 7/23/90  
TYPE OR PRINT NAME W.A. GRESSETT TITLE CONSULTANT DATE 7/23/90

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY MIKE WILLIAMS TITLE SUPERVISOR, DISTRICT II DATE JUL 25 1990

CONDITIONS OF APPROVAL, IF ANY: