

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions
verse side)

BLM DISTRICT
Modified Form No.
HMD60-3160-4

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		3a. Area Code & Phone No. 505/748-1471		5. LEASE DESIGNATION AND SERIAL NO. NM 043625	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210				7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL, 1980' FEL		AUG 23 '90		8. FARM OR LEASE NAME Saguaro AGS Federal Com	
14. PERMIT NO. 30-015-26420		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3616' GR		9. WELL NO. 4	
				10. FIELD AND POOL, OR WILDCAT Und. Morrow	
				11. SEC., T., R., M., OR BLK. AND SUBVY OR AREA Unit J, Sec. 14-T20S-R24E	
				12. COUNTY OR PARISH Eddy	
				13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole with rathole 6:30 PM 8-10-90. Set 40' of 20" conductor. Notified BLM, Carlsbad, NM, answering service of spud. Resumed drilling 14-3/4" hole 3:15 PM 8-11-90. Notified BLM, Carlsbad, NM. Had full returns. Lost circulation at 875'. Regained full returns at 890'. Ran 29 joints 9-5/8" 36# J-55 casing set 1213'. Guide shoe set 1213', insert float set 1172'. Cemented w/900 sx Halliburton Lite w/10%/sx Gilsonite, 1/2#/sx Flocele, 3% CaCl2 (yield 1.98, wt 12.4). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 1:19 PM 8-14-90. Bumped plug to 600 psi, released pressure and float held okay. Circulated 150 sx to pit. WOC. Drilled out 7:19 AM 8-15-90. WOC 18 hrs. NU and tested to 1000 psi for 30 mins. OK. Reduced hole to 8-3/4" and resumed drilling.

Aug 20 8 57 AM '90

RECEIVED

APPROVED FOR RECORD

Ad

AUG 22 1990

CALL CENTER NEW-MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNATURE *Janita S. Rodden*

TITLE Production Supvr.

DATE 8-17-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side