

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OFFICE OF MAMBO
OF COPIES REPORT
(Other Instructions
verue aide)

Modified Form No.
NM60-3160-4

clst

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		3a. Area Code & Phone No. 505/748-1471		8. FARM OR LEASE NAME Alexandre AHX Federal	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION		RECEIVED OCT 11/90 O. G. D. ARTESIA OFFICE		9. WELL NO. 1	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		10. FIELD AND POOL, OR WILDCAT Und. Morrow		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit C, Sec. 33-T19S-R24E	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 2105' FWL, Sec. 33-19S-24E		12. COUNTY OR PARISH Eddy		13. STATE NM	
14. PERMIT NO. 30-015-26427		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3770' GR			

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Ran production casing	X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 8980'. Reached TD 9-18-90. Ran 212 joints 5-1/2" 15.5# & 17# J-55 & N-80 casing set 8980' as follows: 9 jts 5 1/2" 17# N-80, 42 jts 5 1/2" 17# J-55, 127 jts 5 1/2" 15.5# J-55, 22 jts 5 1/2" 17# J-55 and 12 jts 5 1/2" 17# N-80. Float shoe set 8980', float collar set 8936' and DV tool set 5475'. Cemented 1st stagew/1250 sx Class "H" with .4% Halad-22A, .3% CFR-3, 5#/sx salt and 5#/sx Gilsonite with 500 gals superflush (yield 1.18, wt 15.6). PD 10:15 PM 9-21-90. Circulated 150 sacks. Circulate thru DV tool 1-1/2 hrs. Cemented 2nd stage w/1100 sx Halliburton Lite w/1/4# Flocele, 5# Gilsonite (yield 1.84, wt 12.7). Followed w/100 sx Class "H" Neat (yield 1.18, wt 15.60. PD 1:45 PM 9-21-90. WOC. WOCU.

RECEIVED
SEP 28 12 02 PM '90
GARY
AREA

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supvr.

DATE 9-26-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side