

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DEC - 4 1991

WELL API NO.

30-015-26454

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

☒

GAS

WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter B : 660 Feet From The North Line and 1980 Feet From The East Line

Section 1

Township 20S

Range 24E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3592' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 6:15 AM 11-25-91. Set 40' of 20" conductor. Redi-mix to surface. Notified Mike Stubblefield with NMOC, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 12:00 PM NOON 11-26-91. Notified Mike Stubblefield, NMOC, Artesia, NM. TD 14-3/4" hole 1:30 AM 11-28-91. Lost circulation at 825'. Ran 25 joints 9-5/8" 36# J-55 casing set 1086'. Guide shoe set 1086', insert float set 1043'. Cmt'd w/900 sx Pacesetter Lite w/10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.98, wt 12.8). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 6:30 AM 11-28-91. Bumped plug to 1000 psi, released pressure and float held OK. Tag cement 50', redi-mix to surface. WOC. Drilled out 1:00 AM 11-29-91. WOC 18 hrs, 30 minutes. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 12-2-91

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

DEC 13 1991

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: