FIELD REPORT FOR CEMENTING OF WELLS

•

OIL CONSERVATION DIVISION

| Operator Gates | Potr. (| An. | Lease | lt.t. | " | ~"`C | Well # | t | |
|---|---|---|---|------------------------|-------------------|-----------------------------|-------------------------|------------|--------|
| Location of Well | Unit A | Section36 | X | Townshi | | Range | County Cady | | |
| Drilling Contractor Undesig. 19 24 Eddy Type of Equipment Rotary | | | | | | | | | |
| * Witness | | | | | | | | | |
| Size of llole | Size | of Casing | Weigl Foo | | New | or Used | Depth | Socks | Cement |
| <u> 143/4</u> <u> 83/8</u> | * 97 | 8 | 36# | | | | 1200 | 1100 | Circ |
| | | | <u>23</u> # ↔ N- | <u>26</u> # 80 | | | TD | 400 | |
| Casing Data: Surface joints of $\frac{95\%}{100}$ inch 36 # Grade $5-55$ | | | | | | | | | |
| (Approved) (Rejected) | | | | | | | | | |
| Size of hole Type of Shoe TD of hole 12 New-used csg. + 900 sax | <u>1434</u> used <u>ga</u> <u>28</u> Se @ <u>900</u> Pracesor | t 1220 Float c sxs with 20 for life | ollar u t o <u>f 95</u> Ø sa additiv | sed <u>in</u> GInch | <u>sort</u> 36 | Btm 3 jts Grade <u>1</u> | welded | 965 165 | |
| Plug down @ Cement circul | VII | | Date | 1010170 |) | 9 | | 32- 1- | sls |
| Temp. Survey Casing test @ | <u>Western</u> ran @ | <u>ں</u> (AM) (PM (AM) (PM | a) Dat | Witne e e | ssed | by Very top cem | <u>w. Will</u> ent @ | 1 | |
| Method Used | | | | | | | | | |
| 11-01 1 | | | | Witne | ssed | by | | | |
| | | | | | | | | | |
| | <u></u> | | | | | | | · · · | |