

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

NOV 30 '90

WELL API NO.

30-015-26465

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG 1525

7. Lease Name or Unit Agreement Name

State CO Com

8. Well No.

5

9. Pool name or Wildcat

North Dagger Draw Upper Penn

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line

Section 36

Township 19S

Range 24E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3578'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Set retainer, perforate, treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-11-90. Set retainer at 7850'. Stung into retainer. Established injection rate. Squeezed perfs 7867-77' w/125 sx cement. Squeezed to 1500 psi. Pull out of retainer. Circulated 92 sacks to pit. Spotted 500 gals acid thru Canyon Dolomite. Perforated 7806-7828' w/22 - .50" holes as follows: 7806, 10, 12, 14, 16, 18, 20, 22, 24, 26, and 7828'. Swabbed - no oil or gas.

11-15-90. Perforated 7670-7680' and 7742-7774' w/34 - .50" holes as follows; 7670, 72, 74, 76, 78, 80, 7742, 44, 46, 56, 58, 60, 62, 64, 70, 62 and 7774' (2 SPF). Acidized perfs 7670-7774' in two stages w/1400 gals 20% HCL acid. Acidized 7670-7774' w/10000 gals (NEFE) acid plus scale inhibitor and two stages of block.

11-17-90 - 11-19-90. Swabbed and recovered load.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 11-28-90

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

TITLE

DATE

DEC 12 1990

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: