

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

NOV 14 '90

WELL API NO.

30-015-26468

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator

105 South 4th St., Artesia, New Mexico 88210

7. Lease Name or Unit Agreement Name

John AGU

8. Well No.

2

9. Pool name or Wildcat

South Dagger Draw Upper Penn

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line

Section 14 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3609' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 8:30 AM 10-26-90 with rathole. Set 40' of 20" conductor. Notified Betty Rollins, NMOCD, Artesia, of spud. Resumed drilling 14-3/4" hole 8:30 AM 11-1-90. Notified Mike Stubblefield, NMOCD, Artesia. Lost circulation at 96'. Ran 28 jts 9-5/8" 36# J-55 casing set 1222', guide shoe set 1222', insert float set 1179'. Cemented w/900 sx Pacesetter Lite w/10#/sx Hiseal, 1/2#/sx Celloseal, .3% CaCl2 (yield 1.84, wt 12.4). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 9:45 AM 11-4-90. Bumped plug to 600 psi, float held okay. Cement did not circulate. WOC 4 hrs. Ran temp survey and found TOC at 110'. Ran 1". Spotted ready mix to surface. Ok'ed by Darrell Moore, NMOCD. Drilled out 3:45 AM 11-5-90. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes. Reduced hole, resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 11-9-90

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

SUPERVISOR, DISTRICT II

TITLE

DATE

NOV 16 1990

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: