

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-76469

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Jenny Corn

8. Well No.

9. Pool name or Wildcat

n. Sager Draw - Upper Pen

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Conoco Inc.

3. Address of Operator

10 West Drive West McElrath, TX 79705

4. Well Location

Unit Letter E : 1750 Feet From The North Line and 660 Feet From The West Line

Section 17

Township 19S

Range 25E

NMPM

Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: Production Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8 3/4" hole to 8100' (TD). Logged well.
Ran in hole with 188 JTs of 7" 26 #/ft. K-55 casing
to 8099'. First stage of cement: Lead w/ 400 SXS of
class "C" Lite plus 8/10% halad - 9 + 2% CaCl2 + 1/4 #/sk flocele.
Graded by 300 SXS class "H" plus 3% KCl & 6/10% Halad - 9.
Second stage of cement: Lead w/ 425 SXS of class "C" Lite 8/10%
Halad - 9 + 2% CaCl2 + 1/4 #/sk Flocele. Graded by 250 SXS
class "H" plus 3% KCl & 6/10% Halad - 9. Circulated 115 SXS
of cement to surface. Cut off 7" casing. Released rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Nannette Nelson

TITLE

Oil Prod. Analyst

DATE

12-12-90

TYPE OR PRINT NAME

Nannette Nelson

TELEPHONE NO.

(915) 686-6553

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

AUG 30 1991

CONDITIONS OF APPROVAL, IF ANY: