			<u> </u>	151
				Cl
m 3ºau-5 ecombor 1989:	UNITED		RECEIVED	FORM APPROVED Budget Bureau No. (1004)135
eccanes, and	DEPARTMENT OF			5 Lease Designation and Serial No
			CT_ 4 11 OD AN '90	NM-10191
S	SUNDRY NOTICES AND	REPORTS ON WE	.L3	6 If Indian, Allottee or Tribe Name
Do not use this form	n for proposals to drill or • "APPLICATION FOR PE	to deebey or reentry (
			RECEIVED	7. If Unit or CA. Agreement Designation
SUBMIT IN TRIPLICATE				8910115720 East Shugart Unit
Type of Well Dul Gas Well Well (Other	<u></u>	OCT 17 '90	8. Well Name and No. East Shugart #33
Name of Openator	IDO OIL & GAS COMPAN	v /	O. C. D.	9. API Weil No.
Address and Telephone No.	and the second secon		ARTESIA, OMNICE	
P. O. BOX 2208, Roswell, NM 88202 (505)625-6735				10. Field and Pool, or Exploratory Area
Location of Well (Footage,	Sec., T., R., M., or Survey Description	00)		Shugart Yates, 7R, Qn, Grbo 11. County or Parish. State
220	30' FSL & 1680' FWL,	Sec 3/-m185-p31;		
				Eddy, NM
CHECK AI	PPROPRIATE BOX(S) TO	O INDICATE NATUR		
TYPE OF SU	UBMISSION		TYPE OF ACTION	
Notice of 1	Intent			Change of Plans
-				New Construction
Subsequent	1 Report	Plugging Bac		Water Shut-Off
Einst Abar	ndonment Nouce			Conversion to Injection
		Other	-	of muluple completion on Well Completion or
			Recompletion Report	and Log form.)
give subsurface locatio	ons and measured and true vertical dep	pins for all markers and zones pe	tinent to this work.)*	ing any proposed work. If well is directionally druled.
cas	udded well 10:00 PM sing @ 963'. Cement back to surface. W illed out w/ 7 7/8"	ed with 600 sx P NOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas	sing @ 963'. Cement back to surface. W	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plu <mark>s,</mark> 2% Ca	aCl, circulated 160
cas sx Dri	sing @ 963'. Cement back to surface. W illed out w/ 7 7/8"	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste bit 9/30/90.	d 12 1/4" hole to remium Plus, 2% Ca d BOP to 1000# fo: Adu	ACl, circulated 160 r 30 min held okay.
cas sx Dri	sing @ 963'. Cement back to surface. W illed out w/ 7 7/8"	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste	d 12 1/4" hole to remium Plus, 2% Ca d BOP to 1000# fo: Adu	aCl, circulated 160
cas sx Dri 14. hereby cerufy than the f	Sing @ 963'. Cement back to surface. W illed out w/ 7 7/8"	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste bit 9/30/90.	d 12 1/4" hole to remium Plus, 2% Ca d BOP to 1000# fo: Adu	ACl, circulated 160 r 30 min held okay.
cas sx Dri 14. 1 hereby cerufy thatjube f Signed (This space for Federal o Approved by	sing @ 963'. Cement back to surface. W illed out w/ 7 7/8" foregoing is the and correct Configure use	9/28/90. Drille ed with 600 sx P WOC 9 hrs. Teste bit 9/30/90.	d 12 1/4" hole to remium Plus, 2% Ca d BOP to 1000# fo: Adu	ACl, circulated 160 r 30 min held okay.
Cas SX Dri 14. 1 hereby cerufy sharphe f Signed (Thus space for Federal o	sing @ 963'. Cement back to surface. W illed out w/ 7 7/8" foregoing is the and correct Configure use	9/28/90. Drille eed with 600 sx P WOC 9 hrs. Teste bit 9/30/90.	d 12 1/4" hole to remium Plus, 2% Ca d BOP to 1000# fo: Adu	ACl, circulated 160 r 30 min held okay.

v