## Submit 3 Copies to Appropriate District Office

DISTRICT II

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103	
Form C-103 Revised 1-1-89	c $ $

County

DISTRICT P.O. Box 1980, Hobbs, NM 88240

. 1980 Feet From The

Township

19S

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504 2088

30-015-26498
WELL API NO.

Eddy

6. State Oil & Gas Lease No.

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Drawer DD, Artesia, NM 88210

MON 14 '90

24E

**NMPM** 

_		1104	
(	SUNDRY NOTICES AND REPORTS OF DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DESCRIPTION OF THE PROPOSALS (FORM C-101) FOR SUCH PROPOSALS	7. Lease Name or Unit Agreement Name	
1.	Type of Well: OIL GAS WELL X WELL OTHER		Winston "AII"
2	Name of Operator	5) 748-1471	8. Well No.
3.	Address of Operator 105 South 4th St., Artesia, New Mexico	88210	9. Pool name or Wildcat Wildcat Devonian
4.	Well Location E . 1980 Feet From The Nort	h Line and 660	Feet From The West Line

11. Check Appropriate Box to Indicate Nature of Notice, Report, or C				Other	r Data		
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK		PLUG AND ABANDON		REMEDIAL WORK		ALTERING CASING	
TEMPORARILY ABANDON		CHANGE PLANS		COMMENCÉ DRILLING OPNS.	X	PLUG AND ABANDONMENT	r 🔲
PULL OR ALTER CASING				CASING TEST AND CEMENT JO	B X		
OTHER:				OTHER:			

Range

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3657' GR

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole with rathole 11:45 AM 10-24-90. Set 40' of 20" conductor. Notified Johnny Robinson, NMOCD, Artesia, of spud. Resumed drilling 14-3/4" hole 9:30 AM 10-30-90. Notified Betty Rollins, NMOCD, Artesia. Lost circulation 389'. Dry drilled. Ran 28 joints 9-5/8" 36# J-55 casing set 1215'. Guide shoe set 1215', insert float set 1171'. Cemented w/900 sx Halliburton Lite w/10#/sx Gilsonite, 1/2#/sx Flocele and 3% CaCl2 (yield 1.84, wt 12.4). Tail in w/200 sx Calss c w/2% CaCl2 (yield 1.32, wt 14.8). PD 8:30 AM 11-1-90. Bumped plug to 550 psi, held okay. Cement did not circulate. Ran wireline. Tagged cement at 120. Ready mixed to surface (approved by Mike Stubblefield). WOC. NU and tested to 3000 psi for 5 mins. Reduced hole to 8-3/4". Drilled out 2:30 AM 11-2-90. WOC 18 hrs. Resumed drilling.

I hereby certify that the information above is tryle and complete to the best of my know	wiedge and belief.	
SIGNATURE L'ante Dandlin	mme Production Supervisor	DATE
TYPEOR FRINTNAME Juanita Goodlett		TELEPHONE NO. 505/748-1471
(Thus space for State Use) ORIGINAL SIGNED BY		MOV 1 6 1000

MIKE WILLIAMS

SUPERVISOR DISTRICT !!

CONDITIONS OF APPROVAL, IP ANY:

APPROVED BY-