

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

OCT - 8 1991

O. C. D.
ARTESIA OFFICE

WELL API NO.

30-015-26498

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Winston All

8. Well No.

1

9. Pool name or Wildcat

Und. Penasco Draw Permo Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line

Section 14 Township 19S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3657' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate, treat Cisco, test ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-24-91. Installed SV in packer at 8600'. RU. POOH w/tbg. Perforated 6434-6537' w/34 - .50" holes as follows: 6434, 36, 38, 40, 71, 73, 6504, 06, 07, 11, 12, 30, 31, 32, 34, 36 and 6537'. Straddled perfs 6504-37' and acidized w/2500g. 15% acid. Communicated on flush. Moved packer above perfs 6471' to 6473'. Treated w/500g. 15% NEFE acid. Moved RBP to 6460' and tested to 2000 psi. Straddled perfs 6434-6440'. Acidized w/1000g. 15% NEFE acid. Moved RBP below all perfs. Set packer above perforations. Flanged well up. Swabbed to seating nipple.
9-28-91. Acidized perforations 6434-6537' w/20000g. 20% NEFE acid and 45 ball sealers.
10-1-91. Swabbed dry. Installed 1/2" choke with 75 psi. Rigged down.

Well will be dualled or commingled.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett

TITLE Production Supervisor

DATE 10-7-91

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

OCT 10 1991

CONDITIONS OF APPROVAL, IF ANY: