

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

FEB - 4 1991

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line
Section 11 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3607' GR

WELL API NO.
30-015-26545

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Sara AHA Com

8. Well No.
3

9. Pool name or Wildcat
North Dagger Draw Upper Penn

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 3:40 PM 1-10-91 with rathole. Set 40' of 20" conductor and cement to surface with redi-mix. Notified Gary Williams, NMOC, Artesia, NM, of spud. Resumed drilling 17½" hole 11:45 AM 1-13-91. Ran 28 joints 9-5/8" 36# J-55 casing set 1210'. Guide shoe set 1210', insert float set 1169'. Cemented w/150 sx "H" + 12% Thixad (yield 1.24, wt 15.0) and 1000 sx "C" + 10# Hiesal + 3% CaCl2 (yield 2.03, wt 12.5). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 1:00 AM 1-16-91. Bumped plug to 500 psi, float held okay. Circulated 400 sx cement. WOC. Drilled out 7:00 PM 1-16-91. WOC 18 hrs. Reduced hole to 12½" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Production Supervisor

DATE 1-31-91

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 7 1991