

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>YATES Pet. Corp</u>		Lease <u>John AG4</u>		Well # <u>3</u>	
Location of Well	Unit <u>G</u>	Section <u>14</u>	Township <u>20</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor	<u>Underway</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	<u>9 5/8" *</u>	<u>36# J-55</u>		<u>1200</u>	<u>925<sub>5x</sub> Circ.</u>
<u>8 3/4</u>	<u>7"</u>	<u>26# + 23# N-8</u>		<u>TD.</u>	<u>400 5x</u>

## Casing Data:

Surface 28 joints of 9 5/8 inch 36 # Grade J-55(Approved) (Rejected)Inspected by Mike Stubblefield date 12/21/90

## Cementing Program

Size of hole 14 3/4 Size of Casing 9 5/8 Sacks cement required 925Type of Shoe used Guide Float collar used yes Btm 3 jts welded yesTD of hole 1200 Set 1213 Feet of 9 5/8 Inch 36 # Grade J-55New used csg. @ \_\_\_\_\_ with 150 5x sacks neat cement around shoe

+ \_\_\_\_\_ sacks additives \_\_\_\_\_

Plug down @ 4:00 P.M. (AM) (PM) Date 12/22/90Cement circulated to pit No. of Sacks 285 5xCemented by Western Co Witnessed by Gary W. Williams

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: had problems getting 1st four joints in wellOK after that

(Copy)