## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

161	į	
Form C-103	ł	
Form C-103 Revised 1-1-89		
· I		

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

(Thus space for State Use)

CONDITIONS OF AFFROVAL, IF ANY:

ORIGINAL SIGNED BY

SUPERVISOR, DISTRICT IT

MIKE WILLIAMS

## OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO. 30-015-26546

JAN

4 1990

P.O. Drawer DD, Ansain, NM 88210  Santa Fe, New Mexico	5. Indicate Type of Lease STATE FEE X		
DISTRICT III 1000 Rio Brizzos Rd., Aziec, NM 87410	6. State Oil & Gas Lease No.		
SUNDRY NOTICES AND REPORTS ON WE ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPE DIFFERENT RESERVOIR. USE "APPLICATION FOR P (FORM C-101) FOR SUCH PROPOSALS.)	N OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name		
1. Type of Well: OIL GAS WELL X WELL OTHER	John AGU		
2 Name of Operator YATES PETROLEUM CORPORATION (505)	8. Well No. 748–1471 3		
3. Address of Operator 105 South 4th St., Artesia, New Mexico 88	9. Pool same or Wildcat 8210 South Dagger Draw Upper Penn		
4. Well Location  Unit Letter G: 1980 Feet From The North	Line and 1980 Feet From The East Line		
Section 14 Township 20S	Range 24E NMPM Eddy County  er DF, RKB, RT, GR, etc.)		
//////////////////////////////////////			
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING		
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. Z PLUG AND ABANDONMENT		
PULL OR ALTER CASING CASING TEST AND CEMENT JOB			
OTHER:	OTHER:		
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.			
redimix. Notified May Morgan, NMOCD, Artes 10:45 PM 12-19-90. Ran 28 joints 9-5/8" 36 insert float set 1169'. Cemented w/150 sx Pacesetter Lite "C" + 3% CaCl + 10#/sx Hise Tailed in w/200 sx "C" + 2% CaCl (yield 1.3 plug. Float held okay. Cement circulated	t 40' of 20" conductor. Cemented to surface with sia, NM of spud. Resumed drilling 14-3/4" hole if J-55 casing set 1213'. Guide shoe set 1213', "H" + 12% Thixad (yield 1.18, wt 15.6) + 900 sx sal + 1/2#/sx Celloseal (yield 2.03, wt 12.5). 32, wt 14.8). PD 4:15 PM 12-22-90. Did not bump 285 sacks. WOC. Drilled out 7:45 PM 12-23-90. to 3000 psi for 30 minutes, OK. Reduced hole to		
I hereby circify that the information above in true and complete to the best of my knowledge	and belief.		
	Production Supervisor DATE 12-27-90		
TYPEORPRINTNAME Juanita Goodlett	TELEPHONE NO. 505/748-1		
	<del></del>		

TITLE