

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Yates Petr Corp</u>		Lease <u>John "AGU"</u>		Well # <u>3</u>	
Location of Well	Unit <u>G</u>	Section <u>14</u>	Township <u>20</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor	<u>Undesignated</u>		Type of Equipment <u>Rotary</u>		

## APPROVED CASING PROGRAM

\* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	<u>* 9 5/8</u>	<u>36# J-55</u>		<u>1200</u>	<u>925 Circ</u>
<u>8 3/4</u>	<u>7</u>	<u>26# + 23#</u>		<u>TD</u>	<u>400</u>
		<u>N-80</u>			

## Casing Data:

Surface 28 joints of 9 5/8 inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by Mike Stubblefield date 12/21/90

## Cementing Program

Size of hole 14 3/4 Size of Casing 9 5/8 Sacks cement requiredType of Shoe used Guide Float collar used yes Btm 3 jts welded yesTD of hole 1213 Set 1219 Feet of 9 5/8 Inch 36 # Grade J-55New-used csg. @ with 900 sacks neat cement around shoe  
+ Pacesetter 1 1/2 sacks 230cc additivesPlug down @ 4:00 (AM) (PM) Date 12/22/90Cement circulated Yes No. of Sacks 285 SXCemented by Western Witnessed by Gary Williams

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: