

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OFFICE FOR NUMBER
OF COPIES REC
(Other instructions on re-
verse side)

BLM Roswell District
Modified Form No.
NM060-3160-4

0157

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3a. Area Code & Phone No. 505/748-1471		5. LEASE DESIGNATION AND SERIAL NO. NM 045274
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION				6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		RECEIVED FEB 4 1991 O. C. D. ARTESIA, OFFICE		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 660' FEL, Sec. 14-20S-24E				8. FARM OR LEASE NAME Hill View AHE Federal
14. PERMIT NO. 30-015-26602		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3613' GR		9. WELL NO. 8
				10. FIELD AND POOL, OR WILDCAT South Dagger Draw Upper Penn
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit P, Sec. 14-T20S-R24E
				12. COUNTY OR PARISH Eddy
				13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING ☒

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Perforate, Treat

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

2-6-91. Drilled out DV tool at 5419'.

2-7-91. Perforated 7772-7788' w/18 - .40" holes as follows: 7772, 74, 76, 78, 80, 82, 84, 86, and 7788' (2 SPF). Acidized perforations 7772-7788' w/4000 gals 20% NEFE acid.

2-8-91. Perforated 7594-7752' w/50 - .50" holes as follows: 7594, 96, 98, 7604, 06 (2 SPF-10 holes), 7632, 34, 36, 38, (2 SPF-8 holes) 7686, 88, 90, 92 (2 SPF-8 holes), 7730, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, and 7752' (2 SPF-24 holes).

2-9-91. Acidized perforations 7594-7752' w/2500 gals 20% NEFE acid + ball sealers, (4 stages).
Acidized perforations 7594-7752' w/15000 gals 20% NEFE acid + 900# block in two stages. Made 4 runs. Well started flowing.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 2-11-91

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

FEB 15 1991

SJS

*See Instructions on Reverse Side

CARLETON NEWARK