

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Encl. Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

dst
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAR 6 1991

**O. C. D.
ARTESIA OFFICE**

WELL API NO. 30-015-26647
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-1775
7. Lease Name or Unit Agreement Name Wayfarer AIY State
8. Well No. 1
9. Pool name or Wildcat Wildcat Strawn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter P : 990 Feet From The South Line and 660 Feet From The East Line

Section 25 Township 19S Range 29E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3322.6' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 6:30 AM 2-28-91. Notified Mike Stubblefield, NMOCD, Artesia, NM of spud. Ran 9 joints 20" 94# J-55 casing set 370'. Guide shoe set 370', baffle plate set 328'. Cemented w/1000 sx Pacesetter Lite w/10#/sx Gilsonite, 1/2#/sx Celloseal, 3% CaCl2 (yield 1.98, wt 12.4). PD 2:15 AM 3-1-91. Bumped plug to 200 psi, baffle plate did not hold. Cement top at 50'. Redi-mix to surface. WOC. Drilled out 1:00 PM 3-1-91. WOC 10 hrs and 45 mins. Ran 32 joints 13-3/8" 54.5# J-55 casing, set 1372'. Guide shoe set 1372', insert float set 1330'. Cemented w/1100 sx Pacesetter Lite w/10#/sx salt, 5#/sx Gilsonite, 1/2#/sx Celloseal + 1% CaCl2 (yield 1.43, wt 12.6). Tailed in w/300 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 3:15 AM 3-3-91. Bumped plug to 1200 psi, held okay. Circulated 200 sx cement to pit. WOC. Drilled out 11:00 PM 3-3-91. WOC 19 hrs and 15 mins. NU and tested to 1000 psi for 30 minutes. Reduced hole to 12-1/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-5-91

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT I

APPROVED BY _____ TITLE _____ DATE MAR 8 1991

CONDITIONS OF APPROVAL, IF ANY: