State of New Mexico Form C-103 Submit 3 Copies /, Minerals and Natural Resources Department Revised 1-1-89 to Appropriate District Office **OIL CONSERVATION DIVISION DISTRICT I** WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-26647 Santa Fe, New Mexico 87504-2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease RECEIVED STATE X FEE L DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. MAR 1 8 1991 V = 1775SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF PLUID DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" 7. Lease Name or Unit Agreement Name (FORM C-101) FOR SUCH PROPOSALS.) Wayfarer AIY State 1. Type of Well: METT X METT OTHER 2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471 9. Pool name or Wildcat 3. Address of Operator Wildcat Strawn 105 South 4th St., Artesia, New Mexico 88210 Well Location Line and $\underline{-600}$ Feet From The South Feet From The Line Unit Letter Township 19S 29E Eddy thip ¹⁹⁸ Range ^{29E}
10. Elevation (Show whether DF, RKB, RT, GR, etc.) County Section 3322.6' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: ALTERING CASING PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **CHANGE PLANS TEMPORARILY ABANDON** CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** Intermediate Casing OTHER: OTHER:_ 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 3-7-91. Ran 80 joints 8-5/8" 32# J-55 casing, set 3482'. Guide shoe set 3482', float collar set 3438'. Cemented w/1450 sx Pacesetter Lite w/10#/sx Gilsonite, 1/2#/sx Celloseal, 2% CaCl2 (yield 1.98, wt 12.5). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 12:30 PM 3-8-91. Did not bump plug. Cement did not circulate. WOC 24 hrs. Ran temperature survey and found TOC at 1606'. Ran 1". Tag cement 1606'. Spot 200 sx Class C w/3% CaCl2. PD 7:30 AM 3-10-91. WOC 2 hrs. Ran 1". Tag cement 990'. Spot 400 PD 10:45 AM 5-10-91. WOC 8 hrs. Drilled sx Class C Neat. Circulated 5 sacks to pit. out 5:45 AM 3-11-91. WOC 65 hrs and 15 minutes. NU and tested to 1000 psi for 30 minutes. Reduced hole to 7-7/8", and resumed drilling.

	tion above is true and complete to the best of my knowle		
SIGNATURA CLICATI	te Doodles	mme Production Supervisor	DATE3-15-91
TYPEOR PRINT NAME Juanita Goodlett			TELEPHONE NO. 505/748-1471
(This space for State Use)	ORIGINAL SIGNED BY MIKE WILLIAMS		MAR 1 8 1991
APPROVED BY	SUPERVISOR, DISTRICT II	TILE	DATE
CONDITIONS OF APPROVAL, IF	ANY Commence of the second of		