

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brancos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088 RECEIVED
Santa Fe, New Mexico 87504-2088

APR 30 1991

O. C. D.
ARTESIA, OFFICE

WELL API NO.	30-015-216662
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Dagger Draw Com
8. Well No.	10
9. Pool name or Wildcat	N. Dagger Draw - Upper Perm
10. Elevation (Show whether DF, RCL, RT, GR, etc.)	Eddy County

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator

3. Address of Operator

4. Well Location

Unit Letter M : 660 Feet From The South Line and 660 Feet From The West Line

Section 19 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RCL, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: production casing notice ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8 3/4" hole to 8100' (TBS) Logged well.
Ran in hole w/ 186 lbs 7" 26 # K-55 casing to 8096.
First stage of cement w/ 400 SXS class 'c' lite + .0890 Halad 9 + 290 Cacl2, trailed by 250 SXS class # plus
0.590 Halad - 9 + 390 KCL. Circulated 21 Bbls cement.
Second stage of cement w/ 500 SXS 'c' lite + .490 Halad 9 + 290 Cacl2 trailed by 200 SXS class # + .590 Halad 9 + 390 KCL. Circulated 50 SXS cement.
Cut off 7" casing. Released rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Nannette Nelson

TITLE Analyst

DATE April 29th 1991

TYPE OR PRINT NAME Nannette Nelson

TELEPHONE NO. (915) 286-1553

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____

DATE OCT 10 1991

CONDITIONS OF APPROVAL, IF ANY: