

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

dsf
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-26674

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.) RECEIVED

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

DEC 10 1991

2. Name of Operator

YATES PETROLEUM CORPORATION

O. C. D.
ARTESIA OFFICE

8. Well No.

1

3. Address of Operator

105 South 4th St., Artesia, NM 88210

9. Pool name or Wildcat

North Dagger Draw U/Penn

4. Well Location

Unit Letter M : 990 Feet From The South Line and 660 Feet From The West Line

Section 20

Township 19S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3537' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 10:15 AM 11-24-91 with rathole. Set 40' of 20" conductor. Notified Mike Stubblefield, NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 7:30 AM 11-26-91. Notified Mike Stubblefield, NMOCD. Ran 25 jts 9-5/8" 36# J-55 casing set 1086'. Guide shoe set 1086, insert float set 1043'. Cemented w/900 sx Lite with 10#/sx Gilsonite + 1/2#/sx Flocele + 3% CaCl2 (yield 1.84, wt 12.6). Tail in w/200 sx Class "C" with 2% CaCl2 (yield 1.32, wt 14.8). PD 10:45 AM 11-28-91. Did not bump plug, float held OK. Circulated 200 sacks to pit. WOC. Drilled out 4:45 AM 11-29-91. WOC 18 hours. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 12-6-91

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

DEC 18 1991

CONDITIONS OF APPROVAL, IF ANY: