

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Gates Petro Corp.</u>		Lease <u>Ceniga AGZ Com</u>		Well # <u>4</u>	
Location of Well	Unit <u>L</u>	Section <u>12</u>	Township <u>20</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor			Type of Equipment		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4"</u>	<u>9 5/8"</u>	<u>36 # J-55</u>		<u>1200'</u>	<u>circ</u>
<u>8 3/4"</u>	<u>7"</u>	<u>23 - 26 #</u>		<u>TD</u>	

## Casing Data:

Surface            joints of 9 5/8" inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.C. date 4-9-91

## Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required           Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1220' Set 1220' Feet of 2" Inch 36 # Grade J-55(New) used csg. @ 1220' with 200 220 sacks neat cement around shoe+ 900 sax Western Life additives 10 # gilsonite, 1/2 # sx celloscol, 370ccPlug down @ 4945 (AM) (PM) Date 4-10-91Cement circulated No No. of Sacks - 0 -Cemented by Western Company Witnessed by Mike StubblefieldTemp. Survey ran @ 8:30 (AM) (PM) Date 4-10-91 top cement @ 95' \*Casing test @            (AM) (PM) Date           Method Used            Witnessed by           Checked for shut off @            (AM) (PM) Date           Method used            Witnessed by           

Remarks: \* Ready mixed well to surface (3 yards)

Last dry break @ 945'

baskets @ 263'-614'

Last circ. @ 115'