

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87501-2088

APR 15 1991

WELL API NO.

30-015-26689

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator

105 South 4th St., Artesia, New Mexico 88210

4. Well Location

Unit Letter L : 1730 Feet From The South Line and 660 Feet From The West Line

Section 12

Township 20S

Range 24E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3590'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 11:00 AM 4-6-91. Notified Mike Williams, NMOCD, Artesia, NM of spud. Resumed drilling 14-3/4" hole 9:00 PM 4-7-91. Notified Mike Stubblefield, NMOCD. Lost circulation at 115'. Ran 28 joints 9-5/8" 36# J-55 casing set 1220'. Guide shoe set 1220'. Insert float set 1177'. Cemented w/900 sx Pacesetter Lite w/10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl (yield 1.84, wt 12.4). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 4:45 AM 4-10-91. Bumped plug to 1300 psi, released pressure and float held okay. Cement did not circulate. WOC 4 hrs. Ran Temp. Survey and found TOC 95'. Ran 1". Ready mix (6 yds) to surface as instructed by Mike Stubblefield, NMOCD. WOC. Drilled out 11:15 PM 4-10-91. WOC 18 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-11-91

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE APR 18 1991

CONDITIONS OF APPROVAL, IF ANY: