

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 13 1992

O. C. D.
ARTESIA OFFICE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit I, 1980' FSL, 660' FEL, Sec. 26-T20S-R24E

5. Lease Designation and Serial No.

NM 045275

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Conoco AGK Federal #3

9. API Well No.

50-015-26712

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 5:00 PM 4-7-92.. Set 75' of 20" casing and redi-mix to surface. Notified BLM, Carlsbad, NM, of spud. Resumed drilling 14-3/4" hole 5:30 PM 4-25-92. Lost circulation 110', no returns. Drilled with no returns. Ran 27 joints 9-5/8" 36# J-55 casing set at 1177'. Round nose guide shoe set 1177', float collar set 1140'. Cemented w/900 sx Lite + 10# Gilsonite + 1/4# Flocele + 3% CaCl2 (yield 1.99, wt 12.7). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.35, wt 14.8). PD 3:15 AM 4-28-92. Bumped plug to 700 psi, float held OK. Cement did not circulate. Tagged cement at 110'. Ready-mixed to surface at 11:30 AM 4-28-92. WOC. Drilled out 9:15 PM 4-28-92. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes. Reduced hole to 8-3/4" and resumed drilling.

RECEIVED FOR RECORD

MAY 13 1992

ARTESIA, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Production Supervisor

Date 4-30-92

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side