Submit 3 Copies to Appropriate District Office

State of New Mexico Encisy, Minerals and Natural Resources Department

Form C-103 (١.
Revised 1-1-89	•

DISTRICT			
PO Box 1980	Hobbs	NM	88240

OH CONSEDVATION DIRECTIVES

P.O. Box 1980, Hobbs, NM 88240	P.O. Box 208	RR	WELL API NO. 30-015-26719	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	875042088 4 1991	5 Indicate Time of Lance	
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410		O. C. D. ARTESIA, OFFICE	STATE FEE X 6. State Oil & Gas Lease No.	
SUNDRY NOT	ICES AND REPORTS ON WEI	LLS		
(DO NOT USE THIS FORM FOR PRODIFFERENT RESE	OPOSALS TO DRILL OR TO DEEPEN RVOIR. USE "APPLICATION FOR PE :-101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name	
1. Type of Well: OR GAS WELL XX WELL	OTHER		Parish IV Com	
2. Name of Operator YATES PETROLEUM CORPOR	RATION		8. Well No.	
3. Address of Operator			9. Pool name or Wildcat	
105 South 4th St., Art	esia, NM 88210		North Dagger Draw Upper Penn	
4. Well Location	O Feet From The North	Line and1980	Feet From The East Line	
Section 19	7.00	057	NMPM Eddy County	
Secuo	10. Elevation (Show whether		<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>	
<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>	3600'	GR	<u> </u>	
11. Check	Appropriate Box to Indicate	Nature of Notice, Re	eport, or Other Data	
NOTICE OF IN			SEQUENT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS. X PLUG AND ABANDONMENT	
PULL OR ALTER CASING		CASING TEST AND CEMENT JOB X		
OTHER:		OTHER:		
	ations (Clearly state all pertinent details, a	and give pertinent dates, inclu	ding estimated date of starting any proposed	
work) SEE RULE 1103.	thole 8:00 AM 5-18-91.	Set 40' of 20"	conductor. Notified May Morgan	
NMOCD. Artesia. NM. of s	pud. Resumed drilling	14-3/4" hole 4:	00 PM 5-19-91. Notified Mike	
Stubblefield, NMOCD, Art	esia. NM.			
5-21-91. Ran 28 joints	9-5/8" 36# J-55 casing	set 1215'. Gui	de shoe set 1215'. Insert float	
set at 1171'. Cemented	w/900 sx Halliburton Li	ite w/10#/sx Gil	sonite + $1/2\#/\text{sx}$ Floseal + 3%	
CaCl2 (yield 1.84 , wt 12	.4). Tailed in w/200 s	ex Class C w/2%	CaCl2 (yield 1.32, wt 14.8).	
PD 2:45 PM 5-21-91. Bum	ped plug to 600 psi, f	loat held okay.	Cement did not circulate. WOC	
hrs. Ran temperature su	rvey and found TOC at	200'. Kan 1".	Tagged cement at 190'. Spotted	
310 sx Class C w/4% CaCl	2. Circulated 50 sx to) pit. PD 9:00	$\frac{1}{2}$	
	2-91. WUC 26 hrs and	15 minutes. Red	uced hole to 8-3/4" and resumed	
drilling.				
I hereby certify that the information above is t	rue and complete to the best of my knowledge as	nd belief.		
SIGNATURE Canita	Doodless +	mr Production S	upervisor DATE 5-23-91	
	ta Goodlett		ТЕГЕРНОМЕ NO. 505/748-1	
(This space for State Use) ORIGIN	AL SIGNED BY			

47 MAY 2 8 1991 MIKE WILLIAMS

SUPERVISOR, DISTRICT IT APPROVED BY -CONDITIONS OF APPROVAL, IF ANY: