

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 02 1991

O. C. D.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit C, 660' FNL, 1980' FWL, Sec. 23-T20S-R24E

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 043625

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Saguaro AGS Fed. Com #9

9. API Well No.

30-015-26737

10. Field and Pool, or Exploratory Area

So. Dagger Draw Upper Penn

11. County or Parish, State

Eddy, NM

Assoc.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8090'. Reached TD 7-20-91. Ran 197 jts 7" 23# and 26# J-55 and N-80 casing set 8090'. Float shoe set 8090', float collar set 8045'.* Cemented in two stages. Stage 1: 1000 g. WMW1, 1000 g. Superflush 101 followed by 750 sx "H", 5#/CSE, .65 CF-14 +1/4# Celloseal + 5# Gilsonite (yield 1.31, wt 15.0). PD 10:15 PM 7-21-91. Bumped plug to 1800 psi. Opened DV tool with 750 psi. Circ 130 sx. Circ thru DV tool 2-3/4 hrs. Stage 2: 1100 sx Pacesetter Lite "C" + 1/4# Celloseal + 5#/sx salt + 4/10% CF-14 (yield 1.98, wt 12.4). Tailed in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 3:15 AM 7-22-91. Bumped plug and closed tool w/3000 psi. Circ 200 sacks. WOC 24 hrs. Drilled out DV tool at 5657'. Perforated 7617-7760' w/78 .50" holes as follows: 7617, 20, 22, 24, 26, 28, 30, 32, 34 (2 SPF-18 holes), 7662, 64, 66, 70, 72, 74, 76, 78, 80, 86, 88, 90, 92, 94, 96, 98, 7700 (2 SPF-34 holes), 7720, 22, 24, 26, 28, 38, 40, 42, 44, 54, 56, 58, and 7760' (2 SPF-26 holes). Acidized perfs 7617-7760' w/2700 g. 20% NEFE acid 150 ball sealers. Acidize 7617-7760', triple entry, w/25000 g. 20% NEFE acid and 1500# block (1000# rock salt, 500# benzoic acid flakes).

*DV tool @ 5657'.

14. I hereby certify that the foregoing is true and correct

Signed Carla Sead

Title Production Supervisor

Date 7-29-91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

Date 3/5

1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CARLEAD, NEW MEXICO

*See Instruction on Reverse Side