

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon LM 7590 _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres 531 _____	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta 2108 _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs 3320 _____	T. Entrada _____	T. _____
T. Abo 5498 _____	T. 3rd Bone Sprs-5304 _____	T. Wingate _____	T. _____
T. Wolfcamp LM 5924 _____	T. Canyon Dolomite-7624 _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface	5466	5920	454	Sh, Dolo
40	670	630	Redbeds	5920	6300	380	LS, Sh, Dolo
670	1170	500	Dolo, Redbeds	6300	6570	270	LS, Sd, Sh
1170	1470	300	Dolo, Cht, Anhy, Sh	6570	6700	130	Sh
1470	1830	360	Dolo, Cht	6700	6880	180	Sh, LS
1830	3070	1240	Dolo	6880	7440	560	SS, Sh, LS
3070	3180	110	Dolo, Sd, Sh	7440	7600	160	Sh
3180	3450	270	Dolo, Cht, Sd, Sh	7600	8130	530	Dolo, Sh
3450	3610	160	Dolo, LS, Cht	8130	8280	150	Sh, LS
3610	4546	936	LS, Sh				
4546	4640	94	LS, Sh, Dolo				
4640	4850	210	LS, Sh				
4850	4934	84	LS, Dolo				
4934	5310	376	LS, Sh				
5310	5466	156	SS, Sh				