

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 5591950

6. If Indian, Allottee or Tribe Name

54382

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Dagger Draw No. 11

9. API Well No.

30-015-26763

10. Field and Pool, or Exploratory Area

N. Dagger Draw Upper Perm

11. County or Parish, State

Eddy, NM

SUBMIT IN TRIPLICATE

RECEIVED

JUL 11 1991

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

O. C. O.
ARTESIA, OFFICE

3. Address and Telephone No.

10 Desta Drive, Ste 100 W, Midland, TX (915) 686-5494

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL + 1980' FEL, Sect. 30, T-19S, R25E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud / Surf csg
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud 14 3/4" hole at 12:00 am on 6-11-91.

Ran 28 jts 9 5/8" 36# K-55 LT+C csg to 1205'. While csg to wash down csg, the ground washed out from under the BOP stack. The BOP sank out of sight. Washed out hole, could not find BOP. Attempt to fish BOP out of cellar.

Lead w/200 sks Class "C" thickset plus 1/2# 15k floccel, 10# Bilsonite, 1% Cacl2 cmt. middle w/800 sks Class "C" w/12# bilsonite, 6% gel cmt.

2ail w/400 sks Class "C" plus 2% Cacl2 cmt. WOC 7 hrs.

Cut off 9 5/8" cmt bottom of wash out w/549 sks Neat cmt. Install cellar wall + cmt remainder of wash out w/30 yds ready mix. 2st csg to 1000 psi - HELD.

Continue dlog w/8 3/4" bit.

14. I hereby certify that the foregoing is true and correct

Signed Christine A. Neff

Title Admin. Assistant

Date 6-26-91

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date 5/5

1991