		LISY
-N/EB	RECEIVED	
(June 1990) DEPARTME	NITED STATES ENT OF THE INTERIOR AUG 1 9 1991	FORM APPROVED Budget Bureau No. 1004–0135 Expires: March 31, 1993
1 1 1 1 4 1 1 1 1 1 T	F LAND MANAGEMENT O. C. D.	5. Lease Designation and Serial No. NM 0557142
AUG SUNDAT NUTICE	S AND REPORTS ON WELLSARTESIA, OFFICE	6. If Indian, Allottee or Tribe Name
	drill or to deepen or reentry to a different reservoir. OR PERMIT—" for such proposals	
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
I. Type of Well       Oil     Gas       Well     Well       Other		8. Well Name and No.
2. Name of Operator YATES PETROLEUM CORPORATION		Ross EG Federal #4
3. Address and Telephone No.		30-015-26670
105 South 4th St., Artesia, NM 88210 (505) 748-1471		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		North Dagger Draw U/Penn
Unit E, 1980' FNL, 660' FWL,	Sec. 20-T19S-R25E	11. County or Parish, State
		Eddy, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
X Subsequent Report		New Construction
Subsequent Report	Plugging Back Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X <sub>Other</sub> Production Csg, Perfo Treat	
		Completion or Recompletion Report and Log form.)
give subsurface locations and measured and true versions and measured and true versions and measured and true versions a	te all pertinent details, and give pertinent dates, including estimated date of starti entical depths for all markers and zones pertinent to this work.)* 91. Ran 202 joints 7" 26# & 23# J-55 & collar set 8259'. DV tool set 5401'. 5x D42 + .4% D60 + .2% D65 + 5#/sx D44 5acks. Circ thru DV tool 2½ hrs. Sta Ld 1.99, wt 12.6). Tailed in w/100 sx " ced 140 sacks. WOC 18 hrs. Drilled ou CL. Perforated 7792-7897' w/5650" , 18, 7819', 7840, 42, 44, 46, 7947', 7 ' (2 SPF). Acidized perforations in 2 92-7897' w/25000 gals 20% HCL (NEFE and elled bring).	N-80 casing set 8300'. Cemented in two stages. (yield 1.35, wt 15.2). PD ge II - 800 sx Lite + 6% D20 H" (yield 1.18, wt 15.6). t DV tool. Cleaned out to holes as follows: 7792, 94, 874, 76, 78, 80, 82, 84, 86, stages w/4900 gals 20% HCL.
14. I hereby certify that the foregoing is true and correct Signed in a nata in the foregoing is true and correct	Title Production Supervisor	Date8-12-91
(This space for Federal or State office use)		ACCEPTED FOR REGISED
Approved by Conditions of approval, if any:	Tide	DateSJS
		6  99
Title 18 U.S.C. Section 1001, makes it a crime for any per or representations as to any matter within its jurisdiction.	rson knowingly and willfully to make to any department or agency of the Unit	
	*See Instruction on Reverse Side	CARLSBAD, NEW MEXICO

,

.

1