

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

JUL 18 1991

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. D.
ARTESIA, OFFICE

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 1730' FNL & 660' FEL, Section 23-T20S-R24E, NMPM

5. Lease Designation and Serial No.

NM 045274

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hill View AHE Fed. Com #10

9. API Well No.

30-015-26778

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole with rathole 3:30 PM 6-17-91. Set 40' of 20" conductor. Notified BLM, Carlsbad, NM, answering service of spud. Lost circulation 160'. Dry drilling 907'. Ran 28 joints 9-5/8" 36# J-55 casing set 1217'. Guide shoe set 1217', insert float set 1174'. Cemented w/200 sx Class "H" with 12% Thixad + 2% CaCl2 + 700 sx Pacesetter Lite with 10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.98, wt 12.4). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 12:00 AM 6-21-91. Bumped plug to 1000 psi, released pressure and float held OK. Cement did not circulate. WOC 5 hours. Ran Temperature Survey and found TOC @ 130'. Ran 1". Tag cement 130'. Spot 150 sx Class C + 4% CaCl2. PD 5:30 AM 6-21-91. WOC 1 hr. Ran 1". Tag cement 86'. Spot 100 sx Class C + 4% CaCl2. PD 7:00 AM 6-21-91. WOC 11 hrs. Circulated 5 sacks to pit. WOC. Drilled out 11:00 PM 6-21-91. WOC 23 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4" and resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signature [Signature]

Title Production Supervisor

Date 7-8-91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

Date 7-8-91
JUL 15 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

CARLSBAD, NEW MEXICO