

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 02 1991

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No. 335
NM 045274 86241
6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. D.
ARTESIA OFFICE

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 1730' FNL & 660' FEL, Section 23-T20S-R24E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hill View AHE Fed. Com #10

9. API Well No.

30-015-26778

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Squeeze perfs,
reperforate, treat

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-24-91. Set cement retainer at 7798'. Sting into retainer. RU Halliburton and establish injection rate. Pump 50 sx Class H cement w/.8% fluid loss and squeeze perfs 7810-38' to 3100 psi. Sting out of retainer and reverse 2 bbls cement. Perforated 7628-7779' w/84 - .50" holes as follows: 7628, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52 (2 SPF-26 holes), 7690, 92, 94, 96, 98, 7700, 02, 04, 06, 08, 10, 12, 14, 16, 19 (2 SPF-30 holes), 7741, 44, 46, 48, 50 (2 SPF-10 holes), 7758, 60, 62, 64, 66 (2 SPF-10 holes) 7772, 74, 76, and 7779' (2 SPF-8 holes). Acidize perfs 7628-7749' w/2700 gals 20% NEFE acid. Re-acidize 7628-7779' w/22000 gals NEFE acid and 50 ball sealers.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Supervisor

Date 7-29-91

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date 8/5
1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side