

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-26795

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
LG 1525

7. Lease Name or Unit Agreement Name
State CO Com

8. Well No.
6

9. Pool name or Wildcat
North Dagger Draw Upper Penn

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3582' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐ SEP 24 1991

2. Name of Operator
YATES PETROLEUM CORPORATION ✓ O. C. D. ARTESIA OFFICE

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line
Section 36 Township 19S Range 24E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 1:45 PM 9-16-91. Set 40' of 20" conductor. Notified Mike Stubblefield, NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 4:15 PM 9-17-91. Notified Mike Stubblefield, NMOCD. Ran 25 joints 9-5/8" 36# J-55 casing set 1090'. Guide shoe set 1090', insert float set 1046'. Cemented w/800 sx Pacsetter Lite w/10#/sx Gilsonite + 1/2#/sx Celloseal, .3% CaCl2 (yield 1.84, wt 12.6). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.32, wt 14.8). PD 11:15 PM 9-19-91. Bumped plug to 1000 psi, float held OK. Circulated 60 sacks cement. WOC. Drilled out 6:45 PM 9-20-91. WOC 19 hrs and 30 mins. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 9-23-91
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE SEP 26 1991

CONDITIONS OF APPROVAL, IF ANY: