

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
SEP - 9 1991
O. C. D.
ARTESIA OFFICE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION ✓

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit K, 1830' FSL & 1980' FWL, Sec. 23-T20S-R24E

5. Lease Designation and Serial No.

NM 86241

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hill View AHE Fed. Com #11

9. API Well No.

30-015-26810

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 10:00 AM 8-26-91. Set 40' of 20" conductor and cemented to surface with concrete. Notified Jim Amos, BLM, Carlsbad, NM.
Ran 28 jts 9-5/8" 36# J-55 casing set 1220'. Guide shoe set 1220', insert float set 1182'. Cemented w/200 sx "H" + 12% Thixad + 2% CaCl₂ (yield 1.56, wt 14.5) + 700 sx Pacesetter Lite "C" + 10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl₂ (yield 1.94, wt 12.4). Tailed in w/ 200 sx "C" + 2% CaCl₂ (yield 1.32, wt 14.8). PD 7:54 PM 8-29-91. Bumped plug to 800 psi, float held okay. No cement circulated. TOC at 60'. Redi-mix to surface. WOC. Drilled out 2:30 PM 8-30-91. WOC 18 hrs and 36 minutes. Reduced hole to 8-3/4" and resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signature

[Signature]

Title Production Supervisor

Date 9-4-91

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date