

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87501

WELL API NO.

30-015-26821

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator

105 South 4th St., Artesia, New Mexico 88210

4. Well Location

Unit Letter D : 660 Feet From The North Line and 660 Feet From The West Line

Section 29 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3534' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8250'. Reached TD 2-13-92. Ran 199 joints 7" 23# and 26# N-80 and J-55 casing set 8250'. Float shoe set 8250', float collar set 8204'. DV tool set 5569'. Cemented in two stages as follows: 670 sx "P" + 5#/sx Gilsonite, 1/4#/sx Flocele and .6% Halad-14 (yield 1.34, wt 15.1). PD 6:07 PM 2-14-92. Circulated 180 sacks. Circulated thru DV tool 2 hours. Stage II - 850 sx Lite "P" + 5#/sx Gilsonite, 1/4#/sx Flocele + 5#/sx S.H. (yield 1.95, wt 15.0). Tailed in w/100 sx "P" Neat (yield 1.18, wt 15.6). PD 9:00 PM 2-14-92. Circulated 123 sacks. Bumped plug to 2000 psi for 5 mins, float and casing held OK. WOCU 24 hrs.

Drill out DV tool At 5569'. Perforated 7654-7694' w/26 - .50" holes (2 SPF) as follows: 7654, 56, 58, 60, 68, 70, 72, 78, 80, 82, 90, 92, and 7694'. Acidized perms 7654-7694' w/12000g. 20% HCL NEFE acid. Re-acidized perms 7654-7694' w/3000 gals 20% HCL NEFE acid. Swab back load.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-20-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 28 1992